



JOHN DEERE

ENGINE PERFORMANCE CURVE

Rating: Gross Power
 Application: Generator
 1800 RPM (60 Hz)

PowerTech 3.0L Engine

Model: **5030TF270**

72 hp (54 kW) Prime

80 hp (60 kW) Standby

Nominal Engine Power @ 1800 RPM			
Prime		Standby	
HP	kW	HP	kW
72	54	80	60

Generator Efficiency ¹ %	Fan Power		Power Factor	Prime Rating		Standby Rating ²		4 sec Standby Block Load Capability ³
	hp	kW		kW	kVA	kW	kVA	
88*	4.0*	3.0*	0.8	45	56*	50	63*	90%*

Note 1: Est. min. generator efficiency, with 5% fan power loss, to achieve Prime kVA (1500 rpm) / Standby kWe (1800 rpm).
 Note 2: Based on nominal engine power.
 Note 3: Results may vary by alternator and voltage regulator selection. Derate 10% for 100% block load capability.*

Air Intake Restriction 12 in.H₂O (3 kPa)
 Exhaust Back Pressure 30 in.H₂O (7.5 kPa)


Gross power guaranteed within + or - 5% at SAE J1995 and ISO 3046 conditions:

- 77 °F (25 °C) air inlet temperature
- 29.31 in.Hg (99 kPa) barometer
- 104 °F (40 °C) fuel inlet temperature
- 0.853 fuel specific gravity @ 60 °F (15.5 °C)

Conversion factors:

- Power: kW = hp x 0.746
- Fuel: 1 gal = 7.1 lb, 1 L = 0.85 kg
- Torque: N•m = lb-ft x 1.356

All values are from currently available data and are subject to change without notice.



Notes:

Tier-2 Emission Certifications:

Certified by:

CARB; EPA

Ref: Engine Emission Label

Brian L. Carlson
 13 Nov 03

* Revised Data

Curve 5030TF270180080..... Sheet 1 of 2
 November 2003

Engine Specification Data

General Data

Model5030TF270
 Number of Cylinders 5
 Bore and Stroke--in.(mm)..... 3.4 x 4.1 (86 x 105)
 Displacement--in.³ (L)186 (3.05)
 Compression Ratio20.5 : 1*
 Valves per Cylinder--Intake/Exhaust 1 / 1
 Firing Order 1-2-4-5-3
 Combustion System..... Direct Injection
 Engine Type In-line, 4-Cycle
 Aspiration Turbocharged
 Engine Crankcase Vent System Open
 Maximum Crankcase Pressure--in.H₂O (kPa)2 (0.5)

Physical Data

Length--in.(mm)31.5 (799)
 Width--in.(mm)22.3 (566)
 Height--in.(mm)31.5 (800)
 Weight, dry--lb (kg).....633 (287)
 (Includes flywheel housing, flywheel & electrics)
 Center of Gravity Location
 From Rear Face of Block (X-axis)--in.(mm)....9.5 (241)
 Right of Crankshaft (Y-axis)--in.(mm)0.5 (12)
 Above Crankshaft (Z-axis)--in.(mm)4.9 (124)
 Max. Allow. Static Bending Moment at Rear
 Face of Flywhl Hsg w/ 5-G Load--lb-ft (N•m)....369 (500)
 Thrust Bearing Load Limit (Forward)
 Continuous--lb (N) 1147 (5100)
 Intermittent--lb (N).....629 (2800)

Air System

Prime Standby

Maximum Allowable Temp Rise--Ambient Air to
 Engine Inlet--°F (°C) 15 (8) 15 (8)
 Maximum Air Intake Restriction
 Dirty Air Cleaner--in.H₂O (kPa).... 25 (6.25) ...25 (6.25)
 Clean Air Cleaner--in.H₂O (kPa)..... 12 (3) 12 (3)
 Engine Air Flow--ft³/min (m³/min) 162 (4.6)* . 170 (4.8)*
 Intake Manifold Pressure--psi (kPa)...20 (137)* .. 22 (155)*

Cooling System

Prime Standby

Eng. Heat Rejection--BTU/min (kW) ..2100 (37) .. 2265 (40)
 Coolant Flow--gal/min (L/min).....27*(104)* .. 27*(104)*
 Thermostat Start to Open--°F (°C) 180 (82) 180 (82)
 Thermostat Fully Open--°F (°C).....201 (94) 201 (94)
 Maximum Water Pump
 Inlet Restriction--in.H₂O (kPa)28 (7) 28 (7)
 Engine Coolant Capacity--qt (L)3.1 (2.9) 3.1 (2.9)
 Recm'd Pressure Cap--psi (kPa)10 (69) 10 (69)
 Max. Top Tank Temp--°F (°C) 221 (105)* ..221 (105)*
 Min. Coolant Fill Rate--gal/min (L/min) 2.5 (9.5) 2.5 (9.5)
 Min. Air-to-Boil Temperature--°F (°C) .. 117 (47) 117 (47)

Electrical System

12 Volt 24 Volt

Rec'md. Battery Capacity (CCA)--amp750 N/A
 Max. Allow. Starting Circuit Resist.--Ohm ...0.0012 N/A
 Starter Rolling Current
 At 32 °F (0 °C)--amp290 N/A
 At -22 °F (-30 °C)--amp370 N/A

Exhaust System

Prime Standby

Exhaust Flow--ft³/min (m³/min)..... 413 (11.7)...448(12.7)*
 Exhaust Temperature--°F (°C) 963(517)..1020(549)*
 Max. Allow. Back Press.--in.H₂O (kPa).30 (7.5) 30 (7.5)

Fuel System

Prime Standby

Fuel Injection Pump (Stanadyne)..... Unit Pump
 Governor Regulation.....0% 0%
 Governor Type Electrical ... Electrical
 Total Fuel Flow--lb/hr (kg/hr).....185 (84) 185 (84)
 Fuel Consumption--lb/hr (kg/hr)28(12.8) ..32.0(14.3)*
 Maximum Fuel Transfer Pump Suction--
 ft (m) fuel.....10(3.0) 10 (3.0)
 Max. Fuel Inlet Temp.--°F (°C).....185 (85) ...185 (85)*
 Fuel Filter Micron Size @ 98 % Efficiency 5 5

Lubrication System

Prime Standby

Oil Pressure at Rated Speed--psi (kPa)35 (241) ..35 (239)*
 Oil Pressure at Low Idle--psi (kPa) N/A N/A*
 In Pan Oil Temperature--°F (°C) 223 (106) .225 (107)*

Performance Data

Prime Standby

Rated Power--hp (kW) 72 (54) 80 (60)
 Rated Speed--rpm 1800 1800
 Low Idle Speed--rpm N/A* N/A*
 BMEP--psi (kPa) 171 (1176) 190 (1307)
 Friction Power @ Rated Speed--hp (kW)12 (8.9)...12(8.9)*
 Altitude Capability--ft (m) 10,000 (3048)*
 Ratio--Air : Fuel..... 24.2:1* 22.7:1*
 Smoke @ Rated Speed--Bosch No. 1.4* 1.3
 Noise--dB(A) @ 1 m N/A N/A

Fuel Consumption -- lb/hr (kg/h) **Prime* Standby***

25 % Power 7.1 (3.2) 8.9 (4.0)
 50 % Power 14.2 (6.4) 15.6(7.1)
 75 % Power 21.2 (9.6) ...23.3 (10.6)
 100 % Power28.3 (12.8) ...31.5 (14.3)

All values at rated speed and power with standard options unless otherwise noted.

* Revised Data
 Curve 5030TF270180080 Sheet 2 of 2
 November 2003